U.S. Application Serial No. 10/664,578 Attorney Docket: 45565-0012 Reply to Final Office Action of October 19, 2005

Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- (PREVIOUSLY PRESENTED) A compliance device comprising:
- a housing;
- a support block coupled to said housing and movable relative to said housing along a linear axis; and
- a tool holder coupled to said support block and rotatable relative to said support block about a rotational axis;
 - a first biasing assembly urging said tool holder toward a linearly centered position; and a second biasing assembly urging said tool holder to a rotationally centered position.
- 2. (ORIGINAL) The compliance device of claim 1 wherein said rotational axis is substantially perpendicular to said linear axis.
- 3. (ORIGINAL) The compliance device of claim 1 further including a linear slide coupling said support block to said housing, said linear slide having a first member fixed to said housing and a second member fixed to said support block, said second member being linearly movable relative to said first member.
- 4. (PREVIOUSLY PRESENTED) The compliance device of claim 3 wherein said first biasing assembly is coupled to said housing, and operably engages said support block and

Page 2 of 6

please do not Gurer LAT

U.S. Application Serial No. 10/664,578

Attorney Docket: 45565-0012

Reply to Final Office Action of October 19, 2005

said housing, said first biasing assembly urging said support block toward a linearly centered position.

5. (PREVIOUSLY PRESENTED) The compliance device of claim 4 wherein said

second biasing assembly is coupled to said housing and operably engages said tool holder to urge

said tool holder toward a rotationally centered position.

6. (ORIGINAL) The compliance device of claim 5 wherein said second biasing

assembly further includes adjustable stops to limit rotation of said tool holder about said

rotational axis.

7. (ORIGINAL) The compliance device of claim 6 wherein second biasing

assembly further includes first and second dowels fixed to rotate with said tool holder and

biasing elements operably engaging said first dowel to urge said tool holder toward the

rotationally centered position, and wherein said adjustable stops engage said second dowel to

limit rotation of said tool holder about said rotational axis.

8. (ORIGINAL) The compliance device of claim 7 wherein said biasing elements

are spring plungers.

9. (ORIGINAL) The compliance device of claim 8 wherein said adjustable stops are

set screws.

Page 3 of 6

U.S. Application Serial No. 10/664,578 Attorney Docket: 45565-0012

Reply to Final Office Action of October 19, 2005

10. (PREVIOUSLY PRESENTED) A trimming assembly for trimming flash from a workpiece, comprising:

a positioning mechanism;

a compliance device coupled to said positioning mechanism, said compliance device including a housing, a support block coupled to said housing and movable relative to said housing along a linear axis;

a first biasing assembly urging said support block toward a linearly centered position;

a tool holder coupled to said support block and rotatable relative to said support block about a rotational axis; and

a second biasing assembly urging said tool holder to a rotationally centered position.

- 11. (ORIGINAL) The trimming assembly of claim 10 wherein said rotational axis is substantially perpendicular to said linear axis.
- 12. (ORIGINAL) The trimming assembly of claim 10 further including a linear slide coupling said support block to said housing, said linear slide having a first member fixed to said housing and a second member fixed to said support block, said second member being linearly movable relative to said first member.
- 13. (PREVIOUSLY PRESENTED) The trimming assembly of claim 12 wherein said first biasing assembly is coupled to said housing, and operably engages said support block and said housing, and urges said support block toward a linearly centered position, said second biasing assembly coupled to said housing and operably engaging said tool holder.

Page 4 of 6

OCT 28,2005 2:47 PM FR DICKINSON WRIGHT PLLC33 7274 TO 2#075#9157127383 P.08

U.S. Application Serial No. 10/664,578

Attorney Docket: 45565-0012

Reply to Final Office Action of October 19, 2005

14. (ORIGINAL) The trimming assembly of claim 13 wherein second biasing

assembly further includes first and second dowels fixed to rotate with said tool holder, biasing

elements operably engaging said first dowel to urge said tool holder toward the rotationally

centered position, and adjustable stops operably engaging said second dowel to limit rotation of

said tool holder about said rotational axis, wherein said first dowel is spaced from and aligned

with said second dowel.

Claim 15 (CANCELLED)

16. (PREVIOUSLY PRESENTED) The compliance device of claim 1 wherein

said second biasing assembly limits the rotation of said tool holder about said rotational axis.

17. (PREVIOUSLY PRESENTED) The compliance device of claim 1 wherein said

housing includes a cover having an elongated linear slot and wherein said tool holder is disposed

within said linear slot for movement along said linear axis.

18. (PREVIOUSLY PRESENTED) The compliance device of claim 1 wherein said

second biasing assembly includes set screws to adjust the limit of the tool holder's angle of

rotation about said rotational axis.

Claim 19 (CANCELLED)

Page 5 of 6